

### AMENDMENTS TO THE CLAIMS

1. (Previously Presented) A fuel supply for a fuel cell comprising:  
an outer casing containing fuel, and  
an information storage device supported by the casing, said information storage device stores encrypted data that is readable by a controller capable of decoding the encrypted data, wherein said data is encrypted by a manufacturer of the fuel supply.
2. (Original) The fuel supply of claim 1, wherein the data is encrypted and can be decoded by a symmetric-key technique.
3. (Original) The fuel supply of claim 1, wherein the data is encrypted and can be decoded by a public-key technique.
4. (Original) The fuel supply of claim 1, wherein the fuel supply is a fuel cartridge.
5. (Original) The fuel supply of claim 1, wherein the fuel is contained in a liner and the liner is disposed inside the outer casing.
6. (Original) The fuel supply of claim 1, wherein the information storage device comprises an electrically erasable programmable read-only memory.
7. (Previously Presented) The fuel supply of claim 1, wherein the encrypted data is selected from the group consisting of type of cartridge, date the cartridge was manufactured, lot number for the cartridge, sequential identification number assigned to the cartridge, date the information storage device was manufactured, lot number for the information storage device, sequential identification number assigned to the information storage device, machine identification number for the cartridge and/or storage device, shift during which the cartridge and/or storage device were produced, country where the cartridge and/or storage device were produced, facility code

identifying the factory where the cartridge and/or storage device were produced, vibration tolerance for the cartridge and other limits for operating parameter, materials used in manufacturing anti-counterfeit information, fuel information, intellectual property information, safety information, security password, expiration date, shut-down sequence, hot swap procedure, recycling information, reactant information, fuel gage type, fluid sensor information, current fuel level, current ion level in the fuel, number of separations of the cartridge from the fuel cell, number of times that the cartridge was refilled, fuel level on separation of the cartridge from the fuel cell, number of insertions/connections of the cartridge to the fuel cell, fluid level on connection of the cartridge to the fuel cell, maintenance information, marketing information, triggering events, efficiency of the fuel cell and operational history of the fuel cell system.

8. (Currently Amended) A fuel supply for a fuel cell comprising:

an outer casing containing a fuel, and

an information storage device supported by the casing, said information storage device stores data selected from the group of information consisting of a shut-down sequence and hot swap procedure,

wherein the group of information is readable by a controller, and

wherein the controller executes the shut-down sequence when an electronic device that the fuel cell powers or the fuel cell is turned off.

9. (Original) The fuel supply of claim 8, wherein the information storage device comprises an electrically erasable programmable read-only memory.

10. (Original) The fuel supply of claim 9, wherein the group of information is stored on a non-erasable portion of the electrically erasable programmable read-only memory.

11. (Original) The fuel supply of claim 8, wherein the controller is located in the fuel cell.

12. (Original) The fuel supply of claim 8, wherein the controller is located in an electronic

device that the fuel cell powers.

13. (Original) The fuel supply of claim 8, wherein the controller is connected to the information storage device by electrical connections.

14. (Original) The fuel supply of claim 8, wherein the controller is connected to the information storage device by wireless connections.

15. (Original) The fuel supply of claim 8, wherein the fuel supply comprises a fuel cartridge.

16. (Original) The fuel supply of claim 8, wherein the fuel is contained in a liner and the liner is positioned inside the outer casing.

17-18 (Canceled)

19. (Original) The fuel supply of claim 8, wherein the fuel supply is connectable to a pump.

20. (Original) The fuel supply of claim 19, wherein the pump is located inside the fuel cell.

Claims 21-102 (Canceled)

103. (Previously Presented) The fuel supply of claim 8, wherein the information storage device is located in the fuel cell.

104. (Previously Presented) The fuel supply of claim 8, wherein the information storage device is located in an electronic device that the fuel cell powers.

105. (Currently Amended) ~~The fuel supply of claim 8,~~ A fuel supply for a fuel cell comprising:

an outer casing containing a fuel, and  
an information storage device supported by the casing, said information storage device  
stores data selected from the group of information consisting of a shut-down sequence and hot  
swap procedure,

wherein the group of information is readable by a controller, and  
wherein the hot swap procedure comprises instructions for a controller accessing the  
information storage device to switch to an alternate power source for an electronic device that the  
fuel cell powers and to instruct a pump for pumping fuel to the fuel cell to shut down in  
accordance to a predetermined sequence when a trigger event occurs.

106. (Previously Presented) The fuel supply of claim 105, wherein the trigger event comprises a  
removal of a fuel supply containing said fuel for the fuel cell when the electronic device is  
operational.

107. (Previously Presented) The fuel supply of claim 105, wherein the alternate power source  
comprises a battery.

108. (Previously Presented) The fuel supply of claim 105, wherein the alternate power source  
comprises a reserve fuel chamber containing fuel for the fuel cell.

109. (Previously Presented) The fuel supply of claim 105, wherein while using the alternate  
power the controller writes information to the information storage device.

110. (Previously Presented) The fuel supply of claim 105, wherein the predetermined sequence  
comprises running the pump using the alternate power source to pump fuel away from an  
interface between the fuel cell and a fuel supply containing fuel for the fuel cell.

111. (Previously Presented) The fuel supply of claim 8, wherein the hot swap procedure  
comprises semaphore.“lock” and semaphore.“unlock” verbs.

112. (New) The fuel supply of claim 105, wherein the hot swap procedure comprises semaphore.“lock” and semaphore.“unlock” verbs.

113. (New) The fuel supply of claim 8, wherein the shut-down sequence comprises instructions for reducing fuel at the interface of the fuel supply and fuel cell.